

Dx660i CO₂ Laser Coder

Coding with the energy of light

The **Dx660i** delivers outstanding code quality at industry leading speeds*. Ideal for the requirements of high-speed production and future regulatory compliance: larger code contents, serialization, traceability and machine readable code formats.

Meeting Industry 4.0 standards they are ready for today's fast-paced production and integrate seamlessly into your production environment. Options for automated label deployment, remote monitoring, and diagnostics via Domino's cloud-based services help to reduce human intervention, errors and downtime.



Flexibility, Integration and Performance

For line integration:

- ◆ More than 50 standard beam delivery options, a 360° rotatable scanhead, and customization options for specific needs.
- ◆ Seamless integration into ERP, WMS, and MES systems.
- ◆ Web-based user interface and easy operation via an intuitive HMI.

For performance:

- ◆ Advanced coding algorithm increases coding speed* by up to 30% while maintaining superior code quality.

- ◆ Options for coding automation, **R-Series** vision control, and near real-time remote monitoring and diagnostics via Domino's cloud-based services help to ensure only perfectly coded products enter the supply chain.

For tough environments:

- ◆ Dusty, wet, sticky – no problem with IP54/IP65 printheads and IP55 controller for protection.
- ◆ Performs at 45°C ambient temperature.


Permanent traceability coding in excellent quality



PET – ideal for the beverage industry, designed for high production rates and with optional IP65 certification.



Glass – the **Dx660i** codes at speed in excellent quality even on tough substrates.



Films (PP, aluminium) – ideal for pots and stickpacks: large marking fields, pin-sharp small characters, gentle coding that helps keep protective barriers intact.



Cardboard – smart 2D coding that's ready for GSI Sunrise: variable data helps unlock the full potential and supports authentication and anti-counterfeiting.

*Coding speed depends on the individual application; **Dx-Series** has been benchmarked against Domino **D-Series**

www.domino-printing.com

Domino. Do more.



A complete solution

Our services are designed to provide operational insight so you can eliminate downtime and maximize production efficiency.

Operational support

An outstanding level of care, wherever you are. Our **SafeGuard** packages provide high-quality, on-site assistance and AR-enabled remote guidance from our engineers. **SafeGuard** helps to ensure we can be with you when you need us most.

Automatic code inspection

Ensure every code that leaves your factory is present and correct, and free up operator time. With the **R-Series**, Domino's range of vision control systems, you can automate your code inspection to validate code presence, placement, and readability.

Automation

Centralize your label management: **Domino Automation** easily integrates into your manufacturing process as well as your ERP/ MES systems. It makes automatic changeovers safe and simple, helping you to reduce waste and drive sustainability initiatives while increasing productivity and efficiency.


Smart production

Gain operational insight by connecting your printer to Domino's cloud-based services. Obtain production analytics dashboards and receive system error alerts. Our cloud service provides you with the information you need to run your operations more efficiently.

Domino experts at your side

From finding the best solution to installation and support throughout the lifetime of your Domino laser coding systems our experts are at your side.


- ◆ **Testing:** We use a scientific approach to analysing substrates and samples to help ensure that we find the ideal laser for your application.
- ◆ **Safety:** is paramount when operating laser systems: laser guarding, extraction to remove potentially damaging particles, proper installation, prevention of access in operation – we have you covered.
- ◆ **Support:** **Dx-Series** lasers rarely need attention, but if, we're here to help. We utilize AR to troubleshoot issues remotely; if on-site support is needed, our technicians will come prepared to get your line running as fast as possible.



Technical specification Dx-Series Coding System

Laser Type		Dx660i
Laser technology		CO ₂
Laser source		60W, wavelengths 9.3, 10.2, 10.6µm
Expected lifetime		50,000h MTBF
Coding Format		
Coding content		Laser optimized fonts for high-speed marking and standard industrial fonts. Graphics, logos, standard industrial machine readable code (1D, 2D) formats (DataMatrix, GS1, QR). Intuitive GSI Digital Link support. Supporting traceability with serialisation data, sequential and batch numbering. Synchronized clock / Network Time Protocol support (NTP).
Focal length		from 80mm to 600mm
Marking field		from min. 57x57mm ² to max. 379x582mm ²
Advanced Features		Aiming beam, Aim & Code
User Interface		
User Interface		Web based user interface, option to configure multiple parallel access points, optional 10.1" touch panel
Interface Options		Domino Cloud Interface (DCI), Domino Automation
System Specification		
Scan head orientations		Multitude of scan head orientations including 360° rotation and tilt. Scan head can be in various orientation variants. Additionally support for customization and solution integration.
Ingress Protection		Laser Module: IP54 certified fan cooled, optional IP65 certified water cooled Controller: IP55
Operating temperature		5°C - 45°C
Operating humidity		max. 90% RH, non-condensing
Electrical supply		multivoltage 90-264V, 50/60Hz
Input and Outputs, Interfaces		
Inputs/outputs		Multiple inputs and outputs available e.g. extractor, compressed air kit, water chiller, encoder, product detect (NPN, PNP), beacon and interlocks, standard GPIO, additional optional GPIO available.
Interfaces/Protocols		Ethernet, USB, Dynamark Protocol, EtherNet/IP™
Options		
Accessories		Extraction including optimized shrouds, airknife for lens cleaning, multiple brackets, cables and stands for integration support
Certification		Marking: CE**, cTUVus, UKCA / Fulfills requirement: NRTL, ROHS, FDA listed, EMC, FCC

** Partly Completed Machinery as per Machinery Directive (2006/42/EC), CE marking according to ROHS (2011/65/EU) and EMC(2014/30/EU)



TALK TO AN EXPERT

800.444.4512

solutions@domino-na.com

www.domino-na.com